

WHEELS

Product group	Wheels
Item number	59917971
Valid wheel size	500 / 70 R 24
Brand	Nokian
Tread pattern	TRI 2
Valid rim size	DW 16 L x 24
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-10
Rim colour	Black
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	10
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 17426017
LI / SI / PR	164 A8 / 159 D
Load capacity 1 [kg]	5000
Speed 1 [km/h].	40
Load capacity 2 [kg]	4375
Speed 2 [km/h].	65
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted

Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	169,65
ECE regulation number	not necessary
Section width (mm)	515
Stat. radius (SLR) [mm]	585
Speed Radius Index (SRI)	625
Rolling circumference [mm].	3958
Tread depth (mm)	28,0
Tyre capacity 75% [ltr.]	311.25
E-Ready	No
Assembly Item no. Rim	• 31612735
Load capacity of rim 1 [kg]	7500
Speed Rims 1 [km/h]	10
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	10
Maximum air pressure [bar].	4,00
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig

Rim centering	BC
Rim material	steel
RAL	RAL9005
Cavity Sealed	No
Knurling	with knurling
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade