

WHEELS

Product group	Wheels
Item number	59918860
Valid wheel size	400 / 70 R 18
Brand	Michelin
Tread pattern	BibLoad Hard Surface
Valid rim size	13 x 18
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	3075
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Bohnenkamp
Moving Professionals

Technical Informations

Assembly Item no. Tyres	• 13375207
LI / SI / PR	147 A8 / 147 B
Load capacity 1 [kg]	3075
Speed 1 [km/h].	40
Load capacity 2 [kg]	3075
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	95,15
ECE regulation number	not necessary

Section width (mm)	407
Stat. radius (SLR) [mm]	512
Rolling circumference [mm].	3012
Tread depth (mm)	30,0
Tyre capacity 75% [ltr.]	129
E-Ready	No
Assembly Item no. Rim	• 31612165
Load capacity of rim 1 [kg]	4300
Speed Rims 1 [km/h]	30
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,00
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No

Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade