

WHEELS

Product group	Wheels
Item number	59918863
Valid wheel size	340 / 80 R 18
Brand	Alliance
Tread pattern	Multiuse 550
Valid rim size	11 x 18
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	2725
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15284032
LI / SI / PR	143 A8 / 138 D
Load capacity 1 [kg]	2725
Speed 1 [km/h].	40
Load capacity 2 [kg]	2360
Speed 2 [km/h].	65
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	79,65

ECE regulation number	ECE 106
Section width (mm)	343
Stat. radius (SLR) [mm]	450.00
Rolling circumference [mm].	2957
Tread depth (mm)	25,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	106.5
E-Ready	No
Assembly Item no. Rim	• 31612155
Load capacity of rim 1 [kg]	3650
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere

Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade