

WHEELS

Product group	Wheels
Item number	59918881
Valid wheel size	435 / 50 R 19.5
Brand	Bohnenkamp
Tread pattern	Boka Agrar Trans K68
Valid rim size	14.00 x 19.5
Rim connection	6/161/205
Bolt hole design	B2
Rim colour	Silver
Load capacity complete wheel [kg]	4000
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19968005
LI / SI / PR	165 A8 / 161 C
Load capacity 1 [kg]	5150
Speed 1 [km/h].	40
Load capacity 2 [kg]	4625
Speed 2 [km/h].	60
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	112,73
ECE regulation number	ECE 109

Type of retreading	Cold retreaded (tread)
Section width (mm)	440
E-Ready	No
Assembly Item no. Rim	• 30860095
Load capacity of rim 1 [kg]	4000
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	2000
Speed Rims 2 [km/h]	70
Maximum speed [km/h].	70
Maximum air pressure [bar].	9,00
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Preassembled valve	No

TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade