

WHEELS

Product group	Wheels
Item number	59918888
Valid wheel size	435 / 50 R 19.5
Brand	Bohnenkamp
Tread pattern	Boka Agrar Trans K68
Valid rim size	AG 14.00 x 19.5
Rim connection	10/176/225
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	5150
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19968005
LI / SI / PR	165 A8 / 161 C
Load capacity 1 [kg]	5150
Speed 1 [km/h].	40
Load capacity 2 [kg]	4625
Speed 2 [km/h].	60
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	109,53
ECE regulation number	ECE 109

Type of retreading	Cold retreaded (tread)
Section width (mm)	440
E-Ready	No
Assembly Item no. Rim	• 30860140
Load capacity of rim 1 [kg]	5450
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	60
Maximum air pressure [bar].	9,00
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade