

WHEELS

Product group	Wheels
Item number	59918913
Valid wheel size	435 / 50 R 19.5
Brand	Windpower
Tread pattern	PRO TL98
Valid rim size	14.00 x 19.5
Rim connection	6/161/205
Bolt hole design	B2
Rim colour	Silver
Load capacity complete wheel [kg]	2000
Speed complete wheel [km/h]	70



WINDPOWER
Get Your Job Done

Technical Informations

Assembly Item no. Tyres	• 10466690
LI / SI / PR	160 J, 20 PR
Load capacity 1 [kg]	4500
Speed 1 [km/h].	100
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	109,91
Section width (mm)	430

Stat. radius (SLR) [mm]	428.00
Rolling circumference [mm].	2806
Tread depth (mm)	12,0
Rolling resistance	C
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 30860095
Load capacity of rim 1 [kg]	4000
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	2000
Speed Rims 2 [km/h]	70
Maximum speed [km/h].	70
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere

Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade