

WHEELS

Product group	Wheels
Item number	59918919
Valid wheel size	315 / 80 R 22.5
Brand	Bohnenkamp
Tread pattern	Boka Terra
Valid rim size	8.25 x 22.5
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-159
Rim colour	Black
Load capacity complete wheel [kg]	3550
Speed complete wheel [km/h]	35
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19968077
LI / SI / PR	152 / 148 A7
Load capacity 1 [kg]	3550
Speed 1 [km/h].	35
Load capacity 3 [kg]	3075
Speed 3 [km/h].	35
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	114,03

ECE regulation number	not necessary
Type of retreading	Hot retreaded (bead-to-bead)
Section width (mm)	302
Rolling circumference [mm].	3445
Tread depth (mm)	23,0
E-Ready	No
Assembly Item no. Rim	• 39920546
Load capacity of rim 1 [kg]	5100
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4300
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	35
Maximum air pressure [bar].	9,00
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9005

Cavity Sealed	No
Disc thickness [mm]	12
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade