

## WHEELS

Product group	Wheels
Item number	59918922
Valid wheel size	315 / 70 R 22.5
Brand	Bohnenkamp
Tread pattern	Boka Terra
Valid rim size	8.25 x 22.5
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-159
Rim colour	Black
Load capacity complete wheel [kg]	3550
Speed complete wheel [km/h]	35
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 19912089
LI / SI / PR	152 / 148 A7
Load capacity 1 [kg]	3550
Speed 1 [km/h].	35
Load capacity 3 [kg]	3150
Speed 3 [km/h].	35
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	106,03

ECE regulation number	not necessary
Type of retreading	Hot retreaded (bead-to-bead)
Section width (mm)	302
Rolling circumference [mm].	3275
Tread depth (mm)	23,0
E-Ready	No
Assembly Item no. Rim	• 33060212
Load capacity of rim 1 [kg]	5100
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4300
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	35
Maximum air pressure [bar].	8,00
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9005
Cavity Sealed	No

---

<b>Knurling</b>	without knurling
<b>Ventilation holes</b>	No
<b>Verschweißung beidseitig</b>	No
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>TPMS-kompatibles Ventil</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V3.21.1
<b>Valve length [mm]</b>	33.0
<b>Valve angle [°]</b>	gerade