

## WHEELS

Product group	Wheels
Item number	59918924
Valid wheel size	315 / 80 R 22.5
Brand	Windpower
Tread pattern	WDR 37
Valid rim size	9.00 x 22.5
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	3650
Speed complete wheel [km/h]	100



**WINDPOWER**  
Get Your Job Done

## Technical Informations

Assembly Item no. Tyres	• 10466615
LI / SI / PR	154 / 151 M (156 / 150 L), 18 PR
Load capacity 1 [kg]	3750
Speed 1 [km/h].	130
Load capacity 2 [kg]	4000
Speed 2 [km/h].	120
Load capacity 3 [kg]	3450
Speed 3 [km/h].	130
Load capacity 4 [kg]	3350
Speed 4 [km/h].	120
M+S	M+S

3PMSF	3PMSF
Axle position truck	RA
Direction	Left
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	114,83
ECE regulation number	ECE 54 ECE 117
Section width (mm)	320
Stat. radius (SLR) [mm]	508.00
Rolling circumference [mm].	3343
Tread depth (mm)	23,0
Rolling resistance	E
Wet grip	C
Rolling noise [db].	74
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 33060240
Load capacity of rim 1 [kg]	4500
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3650
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	8,30
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel

<b>RAL</b>	RAL9006
<b>Cavity Sealed</b>	No
<b>Ventilation holes</b>	No
<b>Verschweißung beidseitig</b>	No
<b>Rim centering</b>	BC
<b>Number of bolt holes</b>	8
<b>Bolt hole diameter [mm]</b>	21.5
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R16
<b>hub hole diameter [mm].</b>	221
<b>Bolt hole circle diameter [mm]</b>	275
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	9.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V3.20.1
<b>Valve length [mm]</b>	41.0
<b>Valve angle [°]</b>	gerade