

WHEELS

Product group	Wheels
Item number	59919040
Valid wheel size	385 / 65 R 22.5
Brand	Bohnenkamp
Tread pattern	Boka Agrar Trans II
Valid rim size	11.75 x 22.5
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	80
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19968044
LI / SI / PR	160 F
Load capacity 1 [kg]	4500
Speed 1 [km/h].	80
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	129,83
ECE regulation number	not necessary
Type of retreading	Hot retreaded ECO
Section width (mm)	379

Stat. radius (SLR) [mm]	496
E-Ready	No
Assembly Item no. Rim	• 33060267
Load capacity of rim 1 [kg]	4500
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	80
Maximum air pressure [bar].	8,50
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No

Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade