

WHEELS

Product group	Wheels
Item number	59919065
Valid wheel size	385 / 65 R 22.5
Brand	Bohnenkamp
Tread pattern	Boka Agrar Trans I
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	5150
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Bohnenkamp
■ ■ ● Moving Professionals

Technical Informations

Assembly Item no. Tyres	• 19968049
LI / SI / PR	165 D
Load capacity 1 [kg]	5150
Speed 1 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	129,03
ECE regulation number	ECE 109
Type of retreading	Hot retreaded ECO
Section width (mm)	379

Tread depth (mm)	10,0
E-Ready	No
Assembly Item no. Rim	• 33060274
Load capacity of rim 1 [kg]	4500
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	65
Maximum air pressure [bar].	9,00
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade