

## WHEELS

Product group	Wheels
Item number	59919089
Valid wheel size	385 / 65 R 22.5
Brand	Bohnenkamp
Tread pattern	RE Power WP Truck
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	B33
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	110



Bohnenkamp  
■ ■ ● Moving Professionals

## Technical Informations

Assembly Item no. Tyres	• 19968076
LI / SI / PR	160 K
Load capacity 1 [kg]	4500
Speed 1 [km/h].	110
M+S	M+S
3PMSF	3PMSF
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	109,53
ECE regulation number	ECE 109
Type of retreading	Hot retreaded ECO

Section width (mm)	385
Tread depth (mm)	16,0
E-Ready	No
Assembly Item no. Rim	• 31460100
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	110
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	M22 DS 36
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No

---

Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade