

WHEELS

Product group	Wheels
Item number	59919096
Valid wheel size	385 / 65 R 22.5
Brand	Windpower
Tread pattern	WTR 69
Valid rim size	11.75 x 22.5
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	80



WINDPOWER
Get Your Job Done

Technical Informations

Assembly Item no. Tyres	• 10466745
LI / SI / PR	160 K (158 L), 20 PR
Load capacity 1 [kg]	4500
Speed 1 [km/h].	110
Load capacity 2 [kg]	4250
Speed 2 [km/h].	120
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	118,33
ECE regulation number	ECE 54 ECE 117
Section width (mm)	384
Stat. radius (SLR) [mm]	499.00
Rolling circumference [mm].	3260
Tread depth (mm)	16,8
Rolling resistance	C
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 31612560
Load capacity of rim 1 [kg]	5400
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	80
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC

Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade