

WHEELS

Product group	Wheels
Item number	59920610
Valid wheel size	600 / 55 R 22.5
Brand	Alliance
Tread pattern	380
Valid rim size	AG 20.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	4750
Speed complete wheel [km/h]	70



Technical Informations

Assembly Item no. Tyres	• 15215630
LI / SI / PR	165 D / 162 E
Load capacity 1 [kg]	5150
Speed 1 [km/h].	65
Load capacity 2 [kg]	4750
Speed 2 [km/h].	70
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	186,84
ECE regulation number	ECE 106

Section width (mm)	600
Stat. radius (SLR) [mm]	562
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3807
Tread depth (mm)	23,0
Tyre capacity 75% [ltr.]	342
E-Ready	No
Assembly Item no. Rim	• 33060406
Load capacity of rim 1 [kg]	7600
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5600
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	70
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16

hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade