

## WHEELS

|                                   |                |
|-----------------------------------|----------------|
| Product group                     | Wheels         |
| Item number                       | 59922095       |
| Valid wheel size                  | 280 / 80 - 18  |
| Brand                             | Alliance       |
| Tread pattern                     | Tough Trac 325 |
| Valid rim size                    | 9 x 18         |
| Rim connection                    | 6/161/205      |
| Bolt hole design                  | A2             |
| Rim colour                        | Silver         |
| Load capacity complete wheel [kg] | 2000           |
| Speed complete wheel [km/h]       | 40             |



## Technical Informations

|                             |            |
|-----------------------------|------------|
| Assembly Item no. Tyres     | • 15231490 |
| LI / SI / PR                | 132 A8     |
| Load capacity 1 [kg]        | 2000       |
| Speed 1 [km/h].             | 40         |
| Antistatic                  | No         |
| Tyre colour                 | Black      |
| Nettogewicht [kg] (gültig)  | 65,10      |
| ECE regulation number       | ECE 106    |
| Section width (mm)          | 282        |
| Stat. radius (SLR) [mm]     | 411        |
| Rolling circumference [mm]. | 2681       |

|                                |                               |
|--------------------------------|-------------------------------|
| Tread depth (mm)               | 27,0                          |
| Number of lugs                 | 19x2                          |
| E-Ready                        | No                            |
| Assembly Item no. Rim          | • 32010135                    |
| Load capacity of rim 1 [kg]    | 3350                          |
| Speed Rims 1 [km/h]            | 40                            |
| Load capacity of rim 2 [kg]    | 1800                          |
| Speed Rims 2 [km/h]            | 80                            |
| Maximum speed [km/h].          | 40                            |
| Maximum air pressure [bar].    | 4,00                          |
| Type of drive                  | Angetriebene & gezogene Achse |
| Hump                           | kein Hump                     |
| Single / multi-part            | einteilig                     |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Cavity Sealed                  | No                            |
| Ventilation holes              | No                            |
| Verschweißung beidseitig       | No                            |
| Rim centering                  | BC                            |
| Number of bolt holes           | 6                             |
| Bolt hole diameter [mm]        | 21.5                          |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R16                           |
| hub hole diameter [mm].        | 161                           |
| Bolt hole circle diameter [mm] | 205                           |
| Valve seat                     | External Valve                |
| Valve hole diameter [mm]       | 15.7                          |

---

|                         |             |
|-------------------------|-------------|
| Preassembled valve      | No          |
| Valve design            | Metal valve |
| Valve designation ETRTO | V5.01.1     |
| Valve length [mm]       | 50.0        |
| Valve angle [°]         | gerade      |