

## WHEELS

Product group	Wheels
Item number	59926565
Valid wheel size	710 / 70 R 42
Brand	BKT
Tread pattern	Agrimax RT 765M
Valid rim size	DW 23 B x 42
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-30
Rim colour	Silver
Load capacity complete wheel [kg]	7750
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15726977
LI / SI / PR	179 A8 / 176 D
Load capacity 1 [kg]	7750
Speed 1 [km/h].	40
Load capacity 2 [kg]	7100
Speed 2 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	516,83

ECE regulation number	ECE 106
Section width (mm)	716
Stat. radius (SLR) [mm]	922
Rolling circumference [mm].	6174
Tread depth (mm)	58,5
Number of lugs	21x2
E-Ready	No
Assembly Item no. Rim	• 39123150
Load capacity of rim 1 [kg]	9980
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,80
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

---

Knurling	with knurling
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade