

WHEELS

Product group	Wheels
Item number	59926572
Valid wheel size	580 / 70 R 38
Brand	BKT
Tread pattern	Agrimax RT 765
Valid rim size	DW 18 L x 38
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	8000
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 10002953
LI / SI / PR	180 D
Load capacity 1 [kg]	8000
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Direction	Left
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	390,70
ECE regulation number	ECE 106

Section width (mm)	577
Stat. radius (SLR) [mm]	821
Rolling circumference [mm].	5505
Tread depth (mm)	57,5
Number of lugs	20x2
E-Ready	No
Assembly Item no. Rim	• 39122972
Load capacity of rim 1 [kg]	8000
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7040
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,60
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Disc thickness [mm]	15
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade