

## WHEELS

Product group	Wheels
Item number	59926763
Valid wheel size	900 / 60 R 32
Brand	Alliance
Tread pattern	Agristar 375
Valid rim size	TW 27 B x 32
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	+85
Rim colour	Silver
Load capacity complete wheel [kg]	9250
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15226779
LI / SI / PR	185 A8 / 182 D
Load capacity 1 [kg]	9250
Speed 1 [km/h].	40
Load capacity 2 [kg]	8500
Speed 2 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	599,81
ECE regulation number	ECE 106

Section width (mm)	910
Stat. radius (SLR) [mm]	844
Rolling circumference [mm].	5700
Tyre capacity 75% [ltr.]	1074.75
E-Ready	No
Assembly Item no. Rim	• 32013508
Load capacity of rim 1 [kg]	17680
Speed Rims 1 [km/h]	10
Load capacity of rim 2 [kg]	9250
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,20
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

---

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade