

WHEELS

Product group	Wheels
Item number	59927300
Valid wheel size	1050 / 50 R 32
Brand	BKT
Tread pattern	Agrimax RT 600
Valid rim size	36.00 - 32
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	9000
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15727305
LI / SI / PR	184 A8 / 181 B
Load capacity 1 [kg]	9000
Speed 1 [km/h].	40
Load capacity 2 [kg]	8250
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	695,75
ECE regulation number	ECE 106

Section width (mm)	1059
Tread width (mm)	980
Stat. radius (SLR) [mm]	826
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5700
Tread depth (mm)	46,5
Number of lugs	21x2
E-Ready	No
Assembly Item no. Rim	• 32013571
Load capacity of rim 1 [kg]	9250
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	50
Maximum air pressure [bar].	3,20
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	mehrteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No