

## WHEELS

Product group	Wheels
Item number	59931315
Valid wheel size	12.5 - 18
Brand	Alliance
Tread pattern	317
Valid rim size	11 x 18
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	2240
Speed complete wheel [km/h]	90



## Technical Informations

Assembly Item no. Tyres	• 15231078
LI / SI / PR	136 G, 16 PR
Load capacity 1 [kg]	2240
Speed 1 [km/h].	90
Direction	Right
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	69,38
ECE regulation number	ECE 54
Section width (mm)	325
Stat. radius (SLR) [mm]	450

Rolling circumference [mm].	2940
Tread depth (mm)	20,8
Number of lugs	21x2
E-Ready	No
Assembly Item no. Rim	• 33060089
Load capacity of rim 1 [kg]	3850
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3150
Speed Rims 2 [km/h]	90
Maximum speed [km/h].	90
Maximum air pressure [bar].	4,50
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221

---

<b>Bolt hole circle diameter [mm]</b>	275
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade