

## WHEELS

Product group	Wheels
Item number	59931317
Valid wheel size	12.5 - 18
Brand	Alliance
Tread pattern	317
Valid rim size	11 x 18
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	+40
Rim colour	Silver
Load capacity complete wheel [kg]	2240
Speed complete wheel [km/h]	90



## Technical Informations

Assembly Item no. Tyres	• 15231078
LI / SI / PR	136 G, 16 PR
Load capacity 1 [kg]	2240
Speed 1 [km/h].	90
Direction	Right
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	69,38
ECE regulation number	ECE 54
Section width (mm)	325
Stat. radius (SLR) [mm]	450

Rolling circumference [mm].	2940
Tread depth (mm)	20,8
Number of lugs	21x2
E-Ready	No
Assembly Item no. Rim	• 33060101
Load capacity of rim 1 [kg]	3850
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3350
Speed Rims 2 [km/h]	90
Maximum speed [km/h].	90
Maximum air pressure [bar].	4,50
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205

---

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade