

## WHEELS

Product group	Wheels
Item number	59940009
Valid wheel size	260 / 70 R 15.3
Brand	BKT
Tread pattern	AW 712
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	E2
Offset (mm)	+20
Rim colour	Anthrazit
Load capacity complete wheel [kg]	2120
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15717164
LI / SI / PR	134 A8
Load capacity 1 [kg]	2120
Speed 1 [km/h].	40
Carcass properties	Stubble Resistant
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	40,72
ECE regulation number	ECE 106

Section width (mm)	264
Stat. radius (SLR) [mm]	344
Rolling circumference [mm].	2304
Tread depth (mm)	9,5
E-Ready	No
Assembly Item no. Rim	• 32010186
Load capacity of rim 1 [kg]	2360
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	6,00
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL7016
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve

---

Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade