

WHEELS

Product group	Wheels
Item number	59940036
Valid wheel size	560 / 60 R 22.5
Brand	BKT
Tread pattern	Ridemax FL 693 M
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	4750
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15715143
LI / SI / PR	165 D / 162 E
Load capacity 1 [kg]	5150
Speed 1 [km/h].	65
Load capacity 2 [kg]	4750
Speed 2 [km/h].	70
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	169,74
ECE regulation number	ECE 106
Section width (mm)	543
Stat. radius (SLR) [mm]	552
Rolling circumference [mm].	3767
Tread depth (mm)	20,5
E-Ready	No
Assembly Item no. Rim	• 33060373
Load capacity of rim 1 [kg]	7250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,00
Number of bolt holes	8
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Towed axle
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006

Cavity Sealed	No
Disc thickness [mm]	12.0
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade