

WHEELS

Product group	Wheels
Item number	59940073
Valid wheel size	400 / 70 - 24
Brand	BKT
Tread pattern	MP 600
Valid rim size	DW 13 x 24
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+85
Rim colour	Silver
Load capacity complete wheel [kg]	4250
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15731244
LI / SI / PR	158 A8 / 157 B, 18 PR
Load capacity 1 [kg]	4250
Speed 1 [km/h].	40
Load capacity 2 [kg]	4125
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	131,72

ECE regulation number	ECE 106
Section width (mm)	405
Stat. radius (SLR) [mm]	545
Rolling circumference [mm].	3530
Tread depth (mm)	33,5
Number of lugs	18x2
E-Ready	No
Assembly Item no. Rim	• 31612751
Load capacity of rim 1 [kg]	4975
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4250
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,50
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006

Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade