

WHEELS

| | |
|-----------------------------------|----------------|
| Product group | Wheels |
| Item number | 59940082 |
| Valid wheel size | 230 / 95 R 32 |
| Brand | BKT |
| Tread pattern | Agrimax RT 955 |
| Valid rim size | W 8 x 32 |
| Rim connection | 12/517/600 |
| Bolt hole design | B2 |
| Offset (mm) | -42 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 1800 |
| Speed complete wheel [km/h] | 40 |
| RDRA (Reifendruckregelanlage) | No |
| RDKS (Reifendruckkontrollsystem) | No |



Technical Informations

| | |
|----------------------------|----------------|
| Assembly Item no. Tyres | • 15727445 |
| LI / SI / PR | 128 A8 / 128 B |
| Load capacity 1 [kg] | 1800 |
| Speed 1 [km/h]. | 40 |
| Load capacity 2 [kg] | 1800 |
| Speed 2 [km/h]. | 50 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 94,82 |

| | |
|--------------------------------|-------------------------------|
| ECE regulation number | ECE 106 |
| Section width (mm) | 238 |
| Stat. radius (SLR) [mm] | 585 |
| Rolling circumference [mm]. | 3810 |
| Tread depth (mm) | 33,0 |
| Number of lugs | 27x2 |
| E-Ready | No |
| Assembly Item no. Rim | • 39122938 |
| Load capacity of rim 1 [kg] | 2518 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 2216 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 50 |
| Maximum air pressure [bar]. | 4,00 |
| Number of bolt holes | 12 |
| hub hole diameter [mm]. | 517 |
| Bolt hole circle diameter [mm] | 600 |
| Bolt hole diameter [mm] | 21.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| Type of drive | Angetriebene & gezogene Achse |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim centering | BC |
| Rim material | steel |
| Surface treatment | SB |
| RAL | RAL9006 |

| | |
|--------------------------|----------------|
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |
| Valve design | Rubber valve |
| Valve length [mm] | 55.0 |
| Valve angle [°] | gerade |