

WHEELS

Product group	Wheels
Item number	59940086
Valid wheel size	270 / 95 R 32
Brand	Alliance
Tread pattern	350
Valid rim size	W 8 x 32
Rim connection	12/517/600
Bolt hole design	B2
Offset (mm)	-42
Rim colour	Silver
Load capacity complete wheel [kg]	2180
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15226125
LI / SI / PR	135 A8 / 132 D
Load capacity 1 [kg]	2180
Speed 1 [km/h].	40
Load capacity 2 [kg]	2000
Speed 2 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	100,34
ECE regulation number	ECE 106
Section width (mm)	284

Stat. radius (SLR) [mm]	604
Speed Radius Index (SRI)	625
Rolling circumference [mm].	3946
Tread depth (mm)	36,5
Number of lugs	23x2
Tyre capacity 75% [ltr.]	96
E-Ready	No
Assembly Item no. Rim	• 39122938
Load capacity of rim 1 [kg]	2518
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	2216
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	3,60
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
Surface treatment	SB
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	12
Bolt hole diameter [mm]	21.5
Countersinking	Sphere

Spherical countersink [mm].	R16
hub hole diameter [mm].	517
Bolt hole circle diameter [mm]	600
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade