

WHEELS

Product group	Wheels
Item number	59940094
Valid wheel size	710 / 70 R 38
Brand	Alliance
Tread pattern	Forestry 360
Valid rim size	DW 23 B x 38
Rim connection	10/281/335
Offset (mm)	-75
Rim colour	Black
Load capacity complete wheel [kg]	6900
Speed complete wheel [km/h]	10





Technical Informations

Assembly Item no. Tyres	15226809
LI / SI / PR	175 A2 / 168 A8
Load capacity 1 [kg]	6900
Speed 1 [km/h].	10
Load capacity 2 [kg]	5600
Speed 2 [km/h].	40
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	539,76

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



ECE regulation number	ECE 106
Section width (mm)	716
Stat. radius (SLR) [mm]	898
Rolling circumference [mm].	5897
Tread depth (mm)	55,0
Number of lugs	23x2
Tyre capacity 75% [ltr.]	817.5
E-Ready	No
Assembly Item no. Rim •	32100749
Load capacity of rim 1 [kg]	8750
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,40
Number of bolt holes	10
Bolt hole design EUWA	M20
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	24
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSV
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9005
Cavity Sealed	No
Forest reinforcement	flange reinforcement Ø19 mm

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No