

## WHEELS

Product group	Wheels
Item number	59940097
Valid wheel size	650 / 65 R 38
Brand	BKT
Tread pattern	Agrimax RT 657
Valid rim size	TW 20 B x 38
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+175
Rim colour	Silver
Load capacity complete wheel [kg]	5300
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15727190
LI / SI / PR	166 A8 / 163 D
Load capacity 1 [kg]	5300
Speed 1 [km/h].	40
Load capacity 2 [kg]	4875
Speed 2 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	386,45

ECE regulation number	ECE 106
Section width (mm)	645
Tread width (mm)	615
Stat. radius (SLR) [mm]	830
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5483
Tread depth (mm)	59,0
Number of lugs	20x2
E-Ready	No
Assembly Item no. Rim	• 32013641
Load capacity of rim 1 [kg]	5800
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,40
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006

---

Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade