

WHEELS

Product group	Wheels
Item number	59940782
Valid wheel size	520 / 85 R 38
Brand	Alliance
Tread pattern	Agri Star II
Valid rim size	DW 18 L x 38
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+130
Rim colour	Silver
Load capacity complete wheel [kg]	5800
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15228785
LI / SI / PR	169 D
Load capacity 1 [kg]	5800
Speed 1 [km/h].	65
Carcass properties	Stubble Guard
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	332,37
ECE regulation number	ECE 106
Section width (mm)	520
Stat. radius (SLR) [mm]	850

Speed Radius Index (SRI)	875
Rolling circumference [mm].	5588
Tread depth (mm)	55,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	516
E-Ready	No
Assembly Item no. Rim	• 32013639
Load capacity of rim 1 [kg]	5800
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5800
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,60
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade