

WHEELS

Product group	Wheels
Item number	59951210
Valid wheel size	4.50 - 16
Brand	BKT
Tread pattern	TF 8181
Valid rim size	4.00 E x 16
Rim connection	5/67/112
Bolt hole design	E1
Rim colour	Silver
Load capacity complete wheel [kg]	365
Speed complete wheel [km/h]	30
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15721040
LI / SI / PR	73 A6 / 65 A8, 4 PR
Load capacity 1 [kg]	365
Speed 1 [km/h].	30
Load capacity 2 [kg]	290
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	17,58
ECE regulation number	ECE 106

Section width (mm)	122
Stat. radius (SLR) [mm]	311
Rolling circumference [mm].	1952
Tread depth (mm)	11,0
E-Ready	No
Assembly Item no. Rim	• 31610174
Load capacity of rim 1 [kg]	365
Speed Rims 1 [km/h]	30
Load capacity of rim 2 [kg]	290
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,10
Number of bolt holes	5
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No

Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No