

WHEELS

Product group	Wheels
Item number	59965100
Valid wheel size	18 x 8.0 - 10
Brand	Trailermaxx
Tread pattern	M-8001
Valid rim size	6.00 I x 10 H2
Rim connection	4/60/100
Bolt hole design	D12
Offset (mm)	-4
Rim colour	Silver
Load capacity complete wheel [kg]	500
Speed complete wheel [km/h]	140



Technical Informations

Assembly Item no. Tyres	• 10741200
LI / SI / PR	98 N, 6 PR
Load capacity 1 [kg]	750
Speed 1 [km/h].	140
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	12,68
ECE regulation number	ECE 54
Section width (mm)	187
Rolling circumference [mm].	1312
E-Ready	No

Assembly Item no. Rim	• 30855007
Load capacity of rim 1 [kg]	500
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	6,00
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade