

WHEELS

Product group	Wheels
Item number	59967224
Valid wheel size	195 / 55 R 10 C
Brand	Trailermaxx
Tread pattern	CR-966
Valid rim size	6.00 I x 10 H2
Rim connection	5/94/140
Bolt hole design	G1
Offset (mm)	-4
Rim colour	Silver
Load capacity complete wheel [kg]	750
Speed complete wheel [km/h]	140





Technical Informations

Assembly Item no. Tyres •	10765011
LI / SI / PR	98 / 96 P, 10 PR
Load capacity 1 [kg]	750
Speed 1 [km/h].	150
Load capacity 3 [kg]	710
Speed 3 [km/h].	150
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	12,63
ECE regulation number	ECE 54 ECE 117

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Section width (mm)	196
E-Ready	No
Assembly Item no. Rim •	30855002
Load capacity of rim 1 [kg]	750
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	6,25
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	94
Bolt hole circle diameter [mm]	140
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.





Valve angle [°]	gerade

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.