Bohnenkamp Moving Professionals

20.09.2024

WHEELS

| Product group | Wheels |
|-----------------------------------|-----------------|
| Item number | 59967228 |
| Valid wheel size | 195 / 55 R 10 C |
| Brand | Trailermaxx |
| Tread pattern | CR-966 |
| Valid rim size | 6.0 I x 10 H2 |
| Rim connection | 5/67.1/112 |
| Offset (mm) | -4 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 750 |
| Speed complete wheel [km/h] | 140 |





Technical Informations

| Assembly Item no. Tyres | • 10765011 |
|----------------------------|------------------|
| LI / SI / PR | 98 / 96 P, 10 PR |
| Load capacity 1 [kg] | 750 |
| Speed 1 [km/h]. | 150 |
| Load capacity 3 [kg] | 710 |
| Speed 3 [km/h]. | 150 |
| M+S | M+S |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 12,53 |
| ECE regulation number | ECE 54 ECE 117 |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

20.09.2024

| Section width (mm) | 196 |
|--------------------------------|-------------------------------|
| E-Ready | No |
| Assembly Item no. Rim | 39800010 |
| Load capacity of rim 1 [kg] | 1000 |
| Speed Rims 1 [km/h] | 140 |
| Maximum speed [km/h]. | 140 |
| Maximum air pressure [bar]. | 6,25 |
| Type of drive | Angetriebene & gezogene Achse |
| Hump | H2 |
| Single / multi-part | einteilig |
| Rim material | aluminium |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 5 |
| Bolt hole diameter [mm] | 15 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R12 |
| hub hole diameter [mm]. | 67.1 |
| Bolt hole circle diameter [mm] | 112 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 12.5 |
| Preassembled valve | No |
| Valve design | Metal valve |
| Valve length [mm] | 42.0 |
| Valve angle [°] | gerade |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.