Bohnenkamp Moving Professionals

20.09.2024

WHEELS

Product group	Wheels
Item number	59967243
Valid wheel size	195 / 55 R 10 C
Brand	BK Trailer
Tread pattern	204
Valid rim size	6 J x 10 H2
Rim connection	5/67/112
Offset (mm)	-4
Rim colour	Silver
Load capacity complete wheel [kg]	750
Speed complete wheel [km/h]	140



Technical Informations

Assembly Item no. Tyres	18545015
LI / SI / PR	98 / 96 N
Load capacity 1 [kg]	750
Speed 1 [km/h].	140
Load capacity 3 [kg]	710
Speed 3 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	10,58
ECE regulation number	ECE 54

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

20.09.2024

Section width (mm)	201
Stat. radius (SLR) [mm]	213
Rolling circumference [mm].	1418
Tread depth (mm)	6,0
E-Ready	No
Assembly Item no. Rim	39800410
Load capacity of rim 1 [kg]	750
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	6,20
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	aluminium
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.4
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.