

## WHEELS

Product group	Wheels
Item number	59967280
Valid wheel size	21 x 8 - 9
Brand	BKT
Tread pattern	PL 801
Valid rim size	6.00 E - 9
Rim connection	5/110/160
Bolt hole design	A1
Offset (mm)	-10
Rim colour	Silver
Load capacity complete wheel [kg]	1750
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15771080
LI / SI / PR	127 A8, 14 PR
Load capacity 1 [kg]	1750
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	24,03
ECE regulation number	ECE 106
Section width (mm)	200
Tread depth (mm)	19,0
E-Ready	No

Assembly Item no. Rim	• 31695102
Load capacity of rim 1 [kg]	2750
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	1885
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	9,00
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	five-part
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	110
Bolt hole circle diameter [mm]	160
Valve seat	External Valve
Preassembled valve	No