

WHEELS

Product group	Wheels
Item number	59967370
Valid wheel size	6.5 / 80 - 15
Brand	Alliance
Tread pattern	324
Valid rim size	5.5 J x 15 H2
Rim connection	5/66/112
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	750
Speed complete wheel [km/h]	30



Technical Informations

Assembly Item no. Tyres	• 15211600
LI / SI / PR	98 A6 / 94 A8, 6 PR
Load capacity 1 [kg]	750
Speed 1 [km/h].	30
Load capacity 2 [kg]	670
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	22,21
ECE regulation number	ECE 106
Section width (mm)	163

Stat. radius (SLR) [mm]	295
Rolling circumference [mm].	1942
E-Ready	No
Assembly Item no. Rim	• 39600303
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,60
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	17
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	66
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No