

## WHEELS

|                                   |                 |
|-----------------------------------|-----------------|
| Product group                     | Wheels          |
| Item number                       | 59967520        |
| Valid wheel size                  | 205 / 65 R 17.5 |
| Brand                             | Pirelli         |
| Tread pattern                     | ST 01           |
| Valid rim size                    | 6.00 x 17.5     |
| Rim connection                    | 6/161/205       |
| Bolt hole design                  | A2              |
| Rim colour                        | Silver          |
| Load capacity complete wheel [kg] | 1850            |
| Speed complete wheel [km/h]       | 100             |



## Technical Informations

|                         |                           |
|-------------------------|---------------------------|
| Assembly Item no. Tyres | • 13666706                |
| LI / SI / PR            | 129 / 127 J (132 / 132 F) |
| Load capacity 1 [kg]    | 1850                      |
| Speed 1 [km/h].         | 100                       |
| Load capacity 2 [kg]    | 2000                      |
| Speed 2 [km/h].         | 80                        |
| Load capacity 3 [kg]    | 1750                      |
| Speed 3 [km/h].         | 100                       |
| Load capacity 4 [kg]    | 2000                      |
| Speed 4 [km/h].         | 80                        |
| M+S                     | M+S                       |

|                             |                |
|-----------------------------|----------------|
| 3PMSF                       | 3PMSF          |
| Axle position truck         | TR             |
| Antistatic                  | No             |
| Tyre colour                 | Black          |
| Nettogewicht [kg] (gültig)  | 45,53          |
| ECE regulation number       | ECE 54 ECE 117 |
| Section width (mm)          | 207            |
| Stat. radius (SLR) [mm]     | 328            |
| Rolling circumference [mm]. | 2148           |
| Tread depth (mm)            | 11,0           |
| Rolling resistance          | D              |
| Wet grip                    | B              |
| Rolling noise [db].         | 68             |
| Rolling noise level         | A              |
| E-Ready                     | No             |
| Assembly Item no. Rim       | • 33060098     |
| Load capacity of rim 1 [kg] | 2750           |
| Speed Rims 1 [km/h]         | 100            |
| Load capacity of rim 2 [kg] | 2600           |
| Speed Rims 2 [km/h]         | 130            |
| Maximum speed [km/h].       | 100            |
| Maximum air pressure [bar]. | 9,00           |
| Type of drive               | Towed axle     |
| Hump                        | kein Hump      |
| Single / multi-part         | einteilig      |
| Rim material                | steel          |
| RAL                         | RAL9006        |

---

|                                |                |
|--------------------------------|----------------|
| Cavity Sealed                  | No             |
| Ventilation holes              | No             |
| Verschweißung beidseitig       | No             |
| Rim centering                  | BC             |
| Number of bolt holes           | 6              |
| Bolt hole diameter [mm]        | 21.5           |
| Countersinking                 | Sphere         |
| Spherical countersink [mm].    | R16            |
| hub hole diameter [mm].        | 161            |
| Bolt hole circle diameter [mm] | 205            |
| Valve seat                     | External Valve |
| Valve hole diameter [mm]       | 9.7            |
| Preassembled valve             | No             |
| Valve design                   | Metal valve    |
| Valve designation ETRTO        | V3.20.1        |
| Valve length [mm]              | 41.0           |
| Valve angle [°]                | gerade         |