

WHEELS

Product group	Wheels
Item number	59967523
Valid wheel size	205 / 65 R 17.5
Brand	Pirelli
Tread pattern	ST 01
Valid rim size	6.00 x 17.5
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	+70
Rim colour	Silver
Load capacity complete wheel [kg]	1850
Speed complete wheel [km/h]	100



Bohnenkamp
■ ■ ● Moving Professionals

PIRELLI
FASZINATION FAHREN.

Technical Informations

Assembly Item no. Tyres	• 13666706
LI / SI / PR	129 / 127 J (132 / 132 F)
Load capacity 1 [kg]	1850
Speed 1 [km/h].	100
Load capacity 2 [kg]	2000
Speed 2 [km/h].	80
Load capacity 3 [kg]	1750
Speed 3 [km/h].	100
Load capacity 4 [kg]	2000
Speed 4 [km/h].	80
M+S	M+S

3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	45,03
ECE regulation number	ECE 54 ECE 117
Section width (mm)	207
Stat. radius (SLR) [mm]	328
Rolling circumference [mm].	2148
Tread depth (mm)	11,0
Rolling resistance	D
Wet grip	B
Rolling noise [db].	68
Rolling noise level	A
E-Ready	No
Assembly Item no. Rim	• 33060048
Load capacity of rim 1 [kg]	2400
Speed Rims 1 [km/h]	110
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No

Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.5
Valve length [mm]	70.0
Valve angle [°]	27