

WHEELS

Product group	Wheels
Item number	59967524
Valid wheel size	205 / 65 R 17.5
Brand	Pirelli
Tread pattern	ST 01
Valid rim size	6.75 x 17.5
Rim connection	10/176/225
Bolt hole design	B33
Offset (mm)	+133
Half centre distance (HMA) [mm]	145.0
Rim colour	Silver
Load capacity complete wheel [kg]	1850
Speed complete wheel [km/h]	100



Technical Informations

Assembly Item no. Tyres	• 13666706
LI / SI / PR	129 / 127 J (132 / 132 F)
Load capacity 1 [kg]	1850
Speed 1 [km/h].	100
Load capacity 2 [kg]	2000
Speed 2 [km/h].	80
Load capacity 3 [kg]	1750
Speed 3 [km/h].	100
Load capacity 4 [kg]	2000
Speed 4 [km/h].	80

M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	47,54
ECE regulation number	ECE 54 ECE 117
Section width (mm)	207
Stat. radius (SLR) [mm]	328
Rolling circumference [mm].	2148
Tread depth (mm)	11,0
Rolling resistance	D
Wet grip	B
Rolling noise [db].	68
Rolling noise level	A
E-Ready	No
Assembly Item no. Rim	• 39160055
Load capacity of rim 1 [kg]	3750
Speed Rims 1 [km/h]	30
Load capacity of rim 2 [kg]	3000
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006

Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	M22 DS 36
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.4
Valve length [mm]	90.0
Valve angle [°]	27