

## WHEELS

Product group	Wheels
Item number	59967549
Valid wheel size	215 / 75 R 17.5
Brand	Sailun
Tread pattern	SAR1
Valid rim size	6.75 x 17.5
Rim connection	6/161/205
Bolt hole design	B2
Rim colour	Silver
Load capacity complete wheel [kg]	2180
Speed complete wheel [km/h]	120



 **SAILUN**  
TYRE

## Technical Informations

Assembly Item no. Tyres	• 11066114
LI / SI / PR	135 / 133 L, 16 PR
Load capacity 1 [kg]	2180
Speed 1 [km/h].	120
Load capacity 3 [kg]	2060
Speed 3 [km/h].	120
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA TR
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	53,52
ECE regulation number	ECE 54 ECE 117 Vecto Certificate
Section width (mm)	215
Stat. radius (SLR) [mm]	359.31
Rolling circumference [mm].	2260
Tread depth (mm)	12,5
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 30963014
Load capacity of rim 1 [kg]	3135
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3000
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	120
Maximum air pressure [bar].	8,60
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BHC
Number of bolt holes	6

---

<b>Bolt hole diameter [mm]</b>	21.5
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R16
<b>hub hole diameter [mm].</b>	161
<b>Bolt hole circle diameter [mm]</b>	205
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	9.7
<b>Preassembled valve</b>	No