

WHEELS

Product group	Wheels
Item number	59967551
Valid wheel size	215 / 75 R 17.5
Brand	Sailun
Tread pattern	SAR1
Valid rim size	6.75 x 17.5
Rim connection	10/176/225
Bolt hole design	B33
Offset (mm)	+130
Half centre distance (HMA) [mm]	143.0
Rim colour	Silver
Load capacity complete wheel [kg]	2180
Speed complete wheel [km/h]	120



SAILUN
TYRE

Technical Informations

Assembly Item no. Tyres	• 11066114
LI / SI / PR	135 / 133 L, 16 PR
Load capacity 1 [kg]	2180
Speed 1 [km/h].	120
Load capacity 3 [kg]	2060
Speed 3 [km/h].	120
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA TR
Antistatic	No

Tyre colour	Black
Nettogewicht [kg] (gültig)	54,52
ECE regulation number	ECE 54 ECE 117 Vecto Certificate
Section width (mm)	215
Stat. radius (SLR) [mm]	359.31
Rolling circumference [mm].	2260
Tread depth (mm)	12,5
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 30963013
Load capacity of rim 1 [kg]	3000
Speed Rims 1 [km/h]	100
Load capacity of rim 2 [kg]	2757
Speed Rims 2 [km/h]	140
Maximum speed [km/h].	120
Maximum air pressure [bar].	8,60
Number of bolt holes	10
Bolt hole design EUWA	M22 DS 36
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse

Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BHC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
TPMS-kompatibles Ventil	No