

## WHEELS

Product group	Wheels
Item number	59967552
Valid wheel size	235 / 75 R 17.5
Brand	Sailun
Tread pattern	SAR1
Valid rim size	6.75 x 17.5
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+126
Half centre distance (HMA) [mm]	138.0
Rim colour	Silver
Load capacity complete wheel [kg]	2725
Speed complete wheel [km/h]	100



 **SAILUN**  
TYRE

## Technical Informations

Assembly Item no. Tyres	• 11066122
LI / SI / PR	143 / 141 L, 16 PR
Load capacity 1 [kg]	2725
Speed 1 [km/h].	120
Load capacity 3 [kg]	2575
Speed 3 [km/h].	120
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA TR
Antistatic	No

Tyre colour	Black
Nettogewicht [kg] (gültig)	56,81
ECE regulation number	ECE 54 ECE 117
Section width (mm)	235
Stat. radius (SLR) [mm]	372.06
Rolling circumference [mm].	2343
Tread depth (mm)	13,0
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 33060065
Load capacity of rim 1 [kg]	2725
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	8,60
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6

---

<b>Bolt hole diameter [mm]</b>	21.5
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R16
<b>hub hole diameter [mm].</b>	161
<b>Bolt hole circle diameter [mm]</b>	205
<b>Valve seat</b>	Internal Valve
<b>Valve hole diameter [mm]</b>	9.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve length [mm]</b>	54.0
<b>Valve angle [°]</b>	36