

WHEELS

Product group	Wheels
Item number	59967578
Valid wheel size	215 / 75 R 17.5
Brand	Windpower
Tread pattern	WTL 31
Valid rim size	6.75 x 17.5
Rim connection	10/176/225
Bolt hole design	B33
Offset (mm)	+130
Half centre distance (HMA) [mm]	143.0
Rim colour	Silver
Load capacity complete wheel [kg]	2180
Speed complete wheel [km/h]	100



WINDPOWER
Get Your Job Done

Technical Informations

Assembly Item no. Tyres	• 10466411
LI / SI / PR	135 / 133 J, 18 PR
Load capacity 1 [kg]	2180
Speed 1 [km/h].	100
Load capacity 3 [kg]	2060
Speed 3 [km/h].	100
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No

Tyre colour	Black
Nettogewicht [kg] (gültig)	55,80
ECE regulation number	ECE 54 ECE 117
Section width (mm)	228
Stat. radius (SLR) [mm]	351
Rolling circumference [mm].	2310
Tread depth (mm)	12,0
Rolling resistance	D
Wet grip	C
Rolling noise [db].	71
Rolling noise level	A
E-Ready	No
Assembly Item no. Rim	• 30963013
Load capacity of rim 1 [kg]	3000
Speed Rims 1 [km/h]	100
Load capacity of rim 2 [kg]	2757
Speed Rims 2 [km/h]	140
Maximum speed [km/h].	100
Maximum air pressure [bar].	8,30
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No

Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	M22 DS 36
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No