

## WHEELS

Product group	Wheels
Item number	59967601
Valid wheel size	235 / 75 R 17.5
Brand	Windpower
Tread pattern	WTL 31
Valid rim size	6.75 x 17.5
Rim connection	10/176/225
Bolt hole design	B33
Offset (mm)	+133
Half centre distance (HMA) [mm]	145.0
Rim colour	Silver
Load capacity complete wheel [kg]	2725
Speed complete wheel [km/h]	100
Nettogewicht [kg] (gültig)	53,94
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



**WINDPOWER-TYRE**  
*Get Your Job Done*

## Technical Informations

Assembly Item no. Tyres	• 10466415
LI / SI / PR	143 / 141 J, 18 PR
Load capacity 1 [kg]	2725
Speed 1 [km/h].	100
Load capacity 3 [kg]	2575
Speed 3 [km/h].	100
Maximum air pressure [bar].	8,30

Axle position truck	TR
TL/TT	TL
M+S	M+S
3PMSF	3PMSF
Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 54 ECE 117
Rolling resistance	D
Wet grip	B
Rolling noise [db].	69
Rolling noise level	A
Section width (mm)	242
Stat. radius (SLR) [mm]	365.00
Rolling circumference [mm].	2413
Tread depth (mm)	13,0
Assembly Item no. Rim	• 39160055
Load capacity of rim 1 [kg]	3750
Speed Rims 1 [km/h]	30
Load capacity of rim 2 [kg]	3000
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	100
Number of bolt holes	10
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Bolt hole diameter [mm]	26
Bolt hole design EUWA	M22 DS 36

Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BHC
Rim material	steel
RAL	RAL9006
Valve seat	Internal Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201060
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	9.7
Valve design	Metal valve
Valve designation ETRTO	V3.20.4
Valve length [mm]	90.0
Valve angle [°]	27