

WHEELS

| Product group | Wheels |
|-----------------------------------|-----------------|
| Item number | 59967619 |
| Valid wheel size | 215 / 75 R 17.5 |
| Brand | Windpower |
| Tread pattern | WTL 31 |
| Valid rim size | 6.75 x 17.5 |
| Rim connection | 6/161/205 |
| Bolt hole design | B2 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 2180 |
| Speed complete wheel [km/h] | 100 |





Technical Informations

| Assembly Item no. Tyres | 10466411 |
|-------------------------|--------------------|
| LI / SI / PR | 135 / 133 J, 18 PR |
| Load capacity 1 [kg] | 2180 |
| Speed 1 [km/h]. | 100 |
| Load capacity 3 [kg] | 2060 |
| Speed 3 [km/h]. | 100 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | TR |
| Antistatic | No |
| Tyre colour | Black |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



| Nettogewicht [kg] (gültig) | 54,80 |
|-----------------------------|----------------|
| ECE regulation number | ECE 54 ECE 117 |
| Section width (mm) | 228 |
| Stat. radius (SLR) [mm] | 351 |
| Rolling circumference [mm]. | 2310 |
| Tread depth (mm) | 12,0 |
| Rolling resistance | D |
| Wet grip | С |
| Rolling noise [db]. | 71 |
| Rolling noise level | A |
| E-Ready | No |
| Assembly Item no. Rim | 30963014 |
| Load capacity of rim 1 [kg] | 3135 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 3000 |
| Speed Rims 2 [km/h] | 80 |
| Maximum speed [km/h]. | 100 |
| Maximum air pressure [bar]. | 8,30 |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | внс |
| Number of bolt holes | 6 |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



| Bolt hole diameter [mm] | 21.5 |
|--------------------------------|----------------|
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| hub hole diameter [mm]. | 161 |
| Bolt hole circle diameter [mm] | 205 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 9.7 |
| Preassembled valve | No |