

WHEELS

| | |
|-----------------------------------|-----------------|
| Product group | Wheels |
| Item number | 59967622 |
| Valid wheel size | 235 / 75 R 17.5 |
| Brand | Windpower |
| Tread pattern | WTL 31 |
| Valid rim size | 6.75 x 17.5 |
| Rim connection | 6/161/205 |
| Offset (mm) | +65 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 2000 |
| Speed complete wheel [km/h] | 25 |



Bohnenkamp
Moving Professionals

WINDPOWER
Get Your Job Done

Technical Informations

| | |
|-------------------------|--------------------|
| Assembly Item no. Tyres | • 10466415 |
| LI / SI / PR | 143 / 141 J, 18 PR |
| Load capacity 1 [kg] | 2725 |
| Speed 1 [km/h]. | 100 |
| Load capacity 3 [kg] | 2575 |
| Speed 3 [km/h]. | 100 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | TR |
| Antistatic | No |
| Tyre colour | Black |

| | |
|-----------------------------|----------------|
| Nettogewicht [kg] (gültig) | 51,72 |
| ECE regulation number | ECE 54 ECE 117 |
| Section width (mm) | 242 |
| Stat. radius (SLR) [mm] | 365.00 |
| Rolling circumference [mm]. | 2413 |
| Tread depth (mm) | 13,0 |
| Rolling resistance | D |
| Wet grip | B |
| Rolling noise [db]. | 69 |
| Rolling noise level | A |
| E-Ready | No |
| Assembly Item no. Rim | • 30820150 |
| Load capacity of rim 1 [kg] | 2000 |
| Speed Rims 1 [km/h] | 25 |
| Maximum speed [km/h]. | 25 |
| Maximum air pressure [bar]. | 8,30 |
| Type of drive | Towed axle |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 6 |
| Bolt hole diameter [mm] | 19.5 |

| | |
|--------------------------------|----------------|
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| hub hole diameter [mm]. | 161 |
| Bolt hole circle diameter [mm] | 205 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 9.7 |
| Preassembled valve | No |
| Valve design | Metal valve |
| Valve designation ETRTO | V3.20.1 |
| Valve length [mm] | 41.0 |
| Valve angle [°] | gerade |