

## WHEELS

Product group	Wheels
Item number	59967643
Valid wheel size	435 / 50 R 19.5
Brand	Sailun
Tread pattern	STL1
Valid rim size	14.00 x 19.5
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	80



 **SAILUN**  
TYRE

## Technical Informations

Assembly Item no. Tyres	• 11066241
LI / SI / PR	160 J, 20 PR
Load capacity 1 [kg]	4500
Speed 1 [km/h].	100
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	113,20
ECE regulation number	ECE 54 ECE 117

Section width (mm)	438
Stat. radius (SLR) [mm]	430.64
Rolling circumference [mm].	2656
Tread depth (mm)	12,5
Rolling resistance	B
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 31660145
Load capacity of rim 1 [kg]	5400
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	80
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36

---

<b>Bolt hole diameter [mm]</b>	27
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R18
<b>hub hole diameter [mm].</b>	281
<b>Bolt hole circle diameter [mm]</b>	335
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V3.21.1
<b>Valve length [mm]</b>	33.0
<b>Valve angle [°]</b>	gerade