

WHEELS

Product group	Wheels
Item number	59967644
Valid wheel size	235 / 75 R 17.5
Brand	Sailun
Tread pattern	SDR1
Valid rim size	6.75 x 17.5
Rim connection	8/221/275
Bolt hole design	M22
Offset (mm)	+130
Half centre distance (HMA) [mm]	142.0
Rim colour	Silver
Load capacity complete wheel [kg]	2725
Speed complete wheel [km/h]	100



 **SAILUN**
TYRE

Technical Informations

Assembly Item no. Tyres	• 11066121
LI / SI / PR	143 / 141 K, 16 PR
Load capacity 1 [kg]	2725
Speed 1 [km/h].	110
Load capacity 3 [kg]	2575
Speed 3 [km/h].	110
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Antistatic	No

Tyre colour	Black
Nettogewicht [kg] (gültig)	54,93
ECE regulation number	ECE 54 ECE 117
Section width (mm)	233
Stat. radius (SLR) [mm]	372.06
Rolling circumference [mm].	2343
Tread depth (mm)	15,0
Rolling resistance	E
Wet grip	B
Rolling noise [db].	73
Rolling noise level	A
E-Ready	No
Assembly Item no. Rim	• 33060069
Load capacity of rim 1 [kg]	2750
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	8,60
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	HB
Number of bolt holes	8

Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	Internal Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	54.0
Valve angle [°]	36