

## WHEELS

Product group	Wheels
Item number	59967741
Valid wheel size	285 / 70 R 19.5
Brand	Windpower
Tread pattern	WTR 69
Valid rim size	8.25 x 19.5
Rim connection	8/221/275
Bolt hole design	A33
Rim colour	Silver
Load capacity complete wheel [kg]	3350
Speed complete wheel [km/h]	100



**WINDPOWER**  
Get Your Job Done

## Technical Informations

Assembly Item no. Tyres	• 10466456
LI / SI / PR	150 / 148 J, 18 PR
Load capacity 1 [kg]	3350
Speed 1 [km/h].	100
Load capacity 3 [kg]	3150
Speed 3 [km/h].	100
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	69,83
ECE regulation number	ECE 54 ECE 117
Section width (mm)	279
Stat. radius (SLR) [mm]	427.00
Rolling circumference [mm].	2724
Tread depth (mm)	14,0
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 31267874
Load capacity of rim 1 [kg]	3350
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	8,30
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BHC
Number of bolt holes	8
Bolt hole design EUWA	M22 ES 36

---

<b>Bolt hole diameter [mm]</b>	26
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R18
<b>hub hole diameter [mm].</b>	221
<b>Bolt hole circle diameter [mm]</b>	275
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	9.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V3.20.1
<b>Valve length [mm]</b>	41.0
<b>Valve angle [°]</b>	gerade