

WHEELS

Product group	Wheels
Item number	59967791
Valid wheel size	385 / 55 R 22.5
Brand	Windpower
Tread pattern	WGC 28
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	B33
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	100





Technical Informations

Assembly Item no. Tyres	10466591
LI / SI / PR	158 L (160 K), 20 PR
Load capacity 1 [kg]	4250
Speed 1 [km/h].	120
Load capacity 2 [kg]	4500
Speed 2 [km/h].	110
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA RA TR
Antistatic	No
Tyre colour	Black

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Nettogewicht [kg] (gültig)	114,38
ECE regulation number	ECE 54 ECE 117
Section width (mm)	384
Stat. radius (SLR) [mm]	463
Rolling circumference [mm].	3065
Tread depth (mm)	17,0
Rolling resistance	D
Wet grip	В
Rolling noise [db].	74
Rolling noise level	В
E-Ready	No
Assembly Item no. Rim •	10001097
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	13.5
Ventilation holes	Yes
Verschweißung beidseitig	No
Rim centering	внс
Number of bolt holes	10

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No